

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
31 March 2005 (31.03.2005)

PCT

(10) International Publication Number  
**WO 2005/029622 A2**

(51) International Patent Classification<sup>7</sup>: **H01M 8/02**,  
8/04, B60H 1/00

[JP/JP]; 1-43-20, Oooka, Minami-ku, Yokohama-shi,  
Kanagawa, 2320061 (JP).

(21) International Application Number:  
PCT/JP2004/012031

(74) Agent: **GOTO, Masaki**; Shoyu-Kaikan 3-1, Kasumi-  
gaseki 3-chome, Chiyoda-ku, Tokyo, 1000013 (JP).

(22) International Filing Date: 16 August 2004 (16.08.2004)

(81) Designated States (*unless otherwise indicated, for every  
kind of national protection available*): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,  
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,  
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,  
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,  
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2003-328645 19 September 2003 (19.09.2003) JP

(71) Applicant (*for all designated States except US*): NISSAN  
MOTOR CO., LTD. [JP/JP]; 2, Takara-cho, Kana-  
gawa-ku, Yokohama-shi, Kanagawa, 2210023 (JP).


(84) Designated States (*unless otherwise indicated, for every  
kind of regional protection available*): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **OMA, Atsushi**

[Continued on next page]

(54) Title: FUEL CELL POWER PLANT



(57) Abstract: A fuel cell power plant comprises a fuel cell (37) which generates power by an electrochemical reaction between hydrogen supplied to an anode (32A) and oxygen supplied to a cathode (32B) via an electrolyte membrane (32). After the fuel cell (37) has stopped power generation, a cooling device (40, 41) condenses water vapor which has accumulated around the anode (32A). The condensed water prevents hydrogen remaining at the anode (32A) after the fuel cell (37) stops generating power, from burning. The cooling device (40, 41) performs cooling until the fuel cell (37) falls to a predetermined temperature, and then stops operating.

WO 2005/029622 A2



FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *without international search report and to be republished upon receipt of that report*